



- Etches and prepares concrete surfaces for painting.
- Cleans rust and mineral stains from ceramic tile, brick, vitreous china and terrazzo.
- Brightens and removes oxidation (rust) from metals.
- Great for cleaning and brightening metal tools.



SAVOGRAN



Description

The cleaning properties of Crete-Nu are due to its live action as it penetrates into the pores of concrete to lift foreign substances to the surface and remove them.

Application

Use on concrete, ceramic tile, brick, terrazzo, vitreous china and metals. Coverage is approximately 200 sq. ft. per gallon on masonry surfaces and 500 sq ft. on metal and glazed tile. NOT FOR USE on porcelain sinks, tubs, etc.

Directions

Store in a cool place. Read all information on this container before using Crete-Nu. DO NOT use Crete-Nu on hot surfaces or in direct sun. Wear rubber gloves. Protect eyes and skin from splashes. If surfaces are very dirty or greasy, wash with heavy duty detergent solution before applying Crete-Nu.

Concrete: To etch concrete floors, walls, walks, patios, steps, swimming pools, etc. before painting apply full strength Crete-Nu to 15-30 sq. ft. at a time. Work Crete-Nu into surface with a stiff brush for about 10 minutes. Then rinse surface thoroughly with clean water. Allow surface to dry completely before applying finish.

Ceramic tile, brick, terrazzo and vitreous china: To clean and restore to original beauty, use 1 part Crete-Nu to 4 parts water. Rinse thoroughly with clean water.

Metals: To remove rust, oxidation, or to etch all metals (including galvanized), use Crete-Nu full strength. Rinse with clean water and dry quickly. See note below.*

Removing oxidation: Use 1 part Crete-Nu to 3 parts water on copper, brass, boats, shower stalls, radiators, tools, heating, refrigeration and water systems. When possible, soak 1 to 3 hours or sponge until rust, oxidation, oil or grease is removed. Rinse with clean water and dry quickly. See note below.*

Sprinkler heads and aluminum: Use 1 part Crete-Nu to 4 parts water. Soak sprinkler heads in solution to remove scale. Sponge aluminum with solution (DO NOT use Crete-Nu on anodized aluminum). Rinse with clean water and dry quickly. See note below.*

Steam irons and vaporizers: To descale use 1 part Crete-Nu to 8 parts water. Fill chamber and let stand 30 minutes. Flush thoroughly with clean water.

*NOTE: rinse cleaned surfaces thoroughly with clean water before Crete-Nu dries or the residue will reset. Dry metals promptly and protect with light oil, wax or other finish. Cleaned metals begin to rust or oxidize immediately on contact with air.

Important label information

WARNING: HARMFUL IF SWALLOWED OR INHALED. SKIN AND EYE IRRITANT. Before use, always read all information and warnings on container. Material safety data sheets available upon request. Keep out of the reach of children.

Sizes:	Packed:	Universal Product Code:	Ship Wt:
Quart	6/case	0 4954210702 0	17 lbs.
Gallon	4/case	0 4954210703 7	41 lbs.

Consumer Hotline:
800-225-9872