

S.I. No. 7 Coating Remover

PRODUCT DESCRIPTION

This product is a liquid, water rinsable, non-phenolic paint remover formulated for dip tank or flow-on use. Particularly effective nonflammable general purpose remover with a low viscosity profile which provides a minimum of "drag-out" from dip tanks. This results in a short drip interval before wash down.

OUTSTANDING FEATURES

- Nonflammable.
- Especially good at removing conventional coatings.
- Safe to use on all types of wood and metal.
- Minimum drag-out.
- Stripped pieces can be rinsed with water.
- Low evaporation.

CHEMICAL CHARACTERISTICS

Base: Methylene Chloride, Methanol

Appearance: Clear liquid

Odor: Mild

VOC: 105 g/l (excluding exempt Methylene Chloride)

Flash Point: None

Viscosity: 10-15 Seconds/#4 Ford Cup

WPG: 10.33 lbs.

pH (1% in H₂O): 6-7

USE INSTRUCTIONS

This product may be used in immersion process tanks or with a flow on system. The exact time for a particular coating can be determined by testing. Stripped surface should be cleaned with a good cleaner to remove all remover residue.

Savogran offers a customer service lab that will determine optimum immersion time and appropriate cleaning agent upon request.

SAFETY PRECAUTIONS: Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapors. See material safety data sheet for more complete information.

"MANUFACTURER OF SPECIALTY CHEMICAL COMPOUNDS"

P.O. BOX 130, Norwood, MA 02062-0130

Tel. 800-225-9872 Fax. 781-762-1095