

SuperStrip Paint/Varnish Remover



- Heavy-bodied formula clings to vertical, curved or rounded surfaces.
- Cuts faster through tough enamel and polyurethane finishes.
- Penetrates epoxies and marine finishes.
- Non-flammable formula



SAVOGRAN

SuperStrip Paint/Varnish Remover



Description

Savogran's non-flammable, deeper cutting stripper is highly recommended for softening tough finishes: most enamels, epoxy and urethane coatings, paint, varnish, lacquers and marine finishes. Semi-paste formula improves cling and cutting power on vertical surfaces.

Application

Removes multiple layers of paint and varnish without damaging wood, metal and masonry. One gallon of remover covers approximately 100 square feet of surface area. SuperStrip is easily removed with mineral spirits or heavy duty cleaner such as TSP and water.

Directions

Brush on thick coat of remover. Allow remover to work for 15 minutes or more. Scrape test to see if finish is softened to base. If not, wait 15 minutes longer and retest. Be patient and let the remover do the work. Remove sludge with scraper. Use nylon stripping pad and coarse rags to thoroughly wash off residue from stripped surface with mineral spirits or a water solution of heavy duty TSP cleaner.

Important label information

DANGER: POISON! MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. SKIN AND EYE IRRITANT. Before use, always read all information and warnings on container. Material safety data sheets available upon request.

**KEEP OUT OF REACH OF CHILDREN
CLOSE CONTAINER AFTER EACH USE
NEVER STORE IN UNLABELED CONTAINERS**

Stripping Time chart*

Time in minutes	Paint	Varnish, lacquer, shellac	Epoxy, polyurethane	Marine finishes
Strypeeze®	20	15		
Kutzit®	20	15		
SuperStrip®	15	15	25	25
Sprayable Strypeeze®	15	15	25	25
Biodegradable Strypeeze®	30	30	45	30

*Times are approximate and will depend on type of coating and number of coats.

Sizes:	Packed:	Universal Product Code:	Ship Wt.:
Pint	6/case	0 4954201131 0	10 lbs.
Quart	6/case	0 4954201132 7	18 lbs.
Gallon	4/case	0 4954201133 4	45 lbs.
5 Gal.	drum	0 4954204134 8	55 lbs.
55 Gal.	drum	0 4954205135	610 lbs.

