

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 06/13/2024

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Sunnyside Savogram Strypeeze, 01234, 01233, 81233, 01232, 81232

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Paint remover
Restrictions on use : All other uses not recommended above

1.3. Supplier

Sunnyside Corporation
225 Carpenter Avenue
Wheeling, IL 60090
T 800-323-8611

1.4. Emergency telephone number

Emergency number : CHEMTRIC: (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
Acute Tox. 4 (Oral) H302
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 1 H370
STOT SE 3 H336

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : DANGER: POISON!

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor.
H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H370 - Causes damage to organs.

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves, protective clothing, chemical goggles, & face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P307+P311 - If exposed: Call a poison center/doctor.
P312 - Call a poison center or doctor if you feel unwell.
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification

: Methanol, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Acetone	(CAS-No.) 67-64-1	30 – 60
1,3-Dioxolane	(CAS-No.) 646-06-0	30 – 60
1-Butylpyrrolidin-2-one	(CAS-No.) 3470-98-2	1 - 5
Benzyl alcohol	(CAS-No.) 100-51-6	5 – 10
Methyl alcohol	(CAS-No.) 67-56-1	3 – 7

* In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.

First-aid measures after inhalation

: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.

First-aid measures after skin contact

: IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.

First-aid measures after eye contact

: IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.

First-aid measures after ingestion

: IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects

: Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs (optic nerve) (if swallowed).

Symptoms/effects after inhalation

: May cause drowsiness or dizziness.

Symptoms/effects after skin contact

: Causes skin irritation.

Symptoms/effects after eye contact

: Causes serious eye irritation.

Symptoms/effects after ingestion

: Harmful if swallowed.

Chronic symptoms

: Causes damage to organs (optic nerve).

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical. Carbon dioxide (CO₂). Alcohol-resistant foam.

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable extinguishing media : Very low flashpoint: use of water spray might be inefficient for fighting fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : Vapors may cause a flash fire or ignite explosively.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Vapors may travel considerable distance to a source of ignition and flash back. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate all ignition sources if safe to do so. Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Vapors are heavier than air and may travel considerable distances to ignition sources to flash or explode.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Ground equipment electrically. Use only non-sparking tools. Do not touch or walk on the spilled product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Provide good ventilation in process area to prevent formation of vapor. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe vapors. Keep away from sources of ignition - No smoking. Use only non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Ground and bond all transfer and storage equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep container tightly closed in a cool, dry, and well-ventilated place.

Incompatible materials : Strong oxidizing agents. Strong acids. Strong bases.

Heat and ignition sources : Avoid ignition sources. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Benzyl alcohol (100-51-6)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
AIHA	WEEL TWA [ppm]	10 ppm

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1-Butylpyrrolidin-2-one (3470-98-2)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
1,3-Dioxolane (646-06-0)		
ACGIH	ACGIH OEL TWA [ppm]	20 ppm
OSHA	Remark (OSHA)	OELs not established
Methyl alcohol (67-56-1)		
ACGIH	ACGIH OEL TWA	260 mg/m ³
ACGIH	ACGIH OEL TWA [ppm]	200 ppm
ACGIH	ACGIH OEL STEL	328 mg/m ³ recommended Exposure Limit
ACGIH	ACGIH OEL STEL [ppm]	250 ppm recommended Exposure Limit
ACGIH	Regulatory reference	ACGIH 2024
OSHA	OSHA PEL TWA [1]	260 mg/m ³
OSHA	OSHA PEL TWA [2]	200 ppm
OSHA	OSHA PEL STEL [1]	325 mg/m ³
OSHA	OSHA PEL STEL [2]	250 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	6000 ppm
NIOSH	NIOSH REL TWA	260
NIOSH	NIOSH REL TWA [ppm]	200 ppm
NIOSH	NIOSH REL STEL	325 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	250 ppm
NIOSH	Remark (NIOSH)	Eyes, CNS, skin, GI tract, respiratory system
NIOSH	US-NIOSH chemical category	Potential for dermal absorption
Acetone (67-64-1)		
ACGIH	ACGIH OEL TWA [ppm]	250 ppm
ACGIH	ACGIH OEL STEL [ppm]	500 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2023
OSHA	OSHA PEL TWA [1]	2400 mg/m ³
OSHA	OSHA PEL TWA [2]	1000 ppm
OSHA	OSHA PEL STEL [1]	2400 mg/m ³ (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)
OSHA	OSHA PEL STEL [2]	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
IDLH	IDLH [ppm]	2500 ppm (10% LEL)
NIOSH	NIOSH REL TWA	590 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	250 ppm

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Be aware that the chemical may penetrate the gloves. Frequent changes are advisable. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: Strong
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56.11 °C (133 °F)
Flash point	: -17.77 °C (0 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Benzyl alcohol (100-51-6)

LD50 oral rat	1230 mg/kg
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	2 g/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 4178 mg/m ³ (Exposure time: 4 h Source: ECHA_API)

1-Butylpyrrolidin-2-one (3470-98-2)

LD50 oral rat	300 – 2000 mg/kg (Source: NICNAS)
LD50 dermal rat	> 2000 mg/kg (Source: NICNAS)
LC50 Inhalation - Rat	> 5.41 mg/l/4h

1,3-Dioxolane (646-06-0)

LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	8480 mg/kg (Source: NLM_HSDB)
LC50 Inhalation - Rat	68.4 mg/l/4h

Methyl alcohol (67-56-1)

LD50 oral rat	6200 mg/kg
LD50 dermal rabbit	15840 mg/kg (Source: NLM_HSDB)
LC50 Inhalation - Rat [ppm]	22500 ppm/4h

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 15700 mg/kg
LD50 dermal rabbit	> 15700 mg/kg (Source: OECD_SIDS)
LC50 Inhalation - Rat	50100 mg/m ³ (Exposure time: 8 h Source: OECD_SIDS)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
STOT-single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

Benzyl alcohol (100-51-6)

NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs (optic nerve) (if swallowed).
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Harmful if swallowed.
Chronic symptoms	: Causes damage to organs (optic nerve).

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment. Empty containers retain product residue and can be hazardous.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT)

: UN1263 Paint related material, 3, II

UN-No.(DOT)

: UN1263

Proper Shipping Name (DOT)

: Paint related material

Class (DOT)

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT)

: II - Medium Danger

Hazard labels (DOT)

: 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea (IMDG)

Transport document description (IMDG) : UN 1263 PAINT RELATED MATERIAL, 3, II

UN-No. (IMDG) : 1263

Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 5 L

Air transport (IATA)

Transport document description (IATA) : UN 1263 Paint related material, 3, II

UN-No. (IATA) : 1263

Proper Shipping Name (IATA) : Paint related material

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Sunnyside Savogram Strypeeze

All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Acute toxicity (any route of exposure) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
-------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

1-Butylpyrrolidin-2-one (3470-98-2)

EPA TSCA Regulatory Flag	PMN - PMN - indicates a commended PMN substance. S - S - indicates a substance that is identified in a final Significant New Use Rule. 5E - 5E - indicates a substance that is the subject of a TSCA section 5E order. Subject to TSCA 12(b) export notification requirements. See 40 CFR 721.11150 for conditions of the SNUR.
--------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methyl alcohol (67-56-1)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	5000 lb
-----------	---------

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Methyl alcohol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Sunnyside Savogram Strypeeze

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Methyl alcohol (67-56-1)		X				47000 µg/day (inhalation); 23,000 µg/day (oral)

Component	State or local regulations
Benzyl alcohol (100-51-6)	U.S. - Pennsylvania - RTK (Right to Know) List
Methyl alcohol (67-56-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List; U.S. - Massachusetts - Right To Know List
Acetone (67-64-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
1,3-Dioxolane (646-06-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List


SECTION 16: Other information

Other information : Author: EMA.

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS Hazard Rating

Health : 3*
* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 3
Physical : 0

Indication of changes:

Revision 1.0: New SDS Created.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.